Vehicle lighting manufacturer



www.fristom.com

FT-078 LED

2-functional **LED** clearance lamp

lamps FUNCTIONS:

clearance light

Depending on the light color:

- front clearance light white
- rear clearance light red
- side clearance light yellow
- Vertical / horizontal approval

Power consumption:

- front clearance light: 12V/24V = 0.055A/0.055A
- rear clearance light: 12V/24V = 0.165A/0.165A
- side clearance light: 12V/24V = 0.055A/0.055A

Power consumption / Rated power:

- front clearance light: 12V/24V = 0.7W/1.4W
- rear clearance light: 12V/24V = 2W/4W
- side clearance light: 12V/24V = 0.7W/1.4W




































SET CONTAINS:

- side marker lamp
- flat mounting pad
- angled bracket
- mounting screws

FT-078 B LED	Clearance Lamp LED 12-36V, WHITE with reflector, flat mounting and angle bracket, a loom lenght 0,5m.
FT-078 B LED QS075	Clearance Lamp LED 12-36V, WHITE with reflector, flat mounting and angle bracket, a loom lenght 0,5m and connector QS075.
FT-078 B LED QS150	Clearance Lamp LED 12-36V, WHITE with reflector, flat mounting and angle bracket, a loom lenght 0,5m and connector QS150.
FT-078 C LED	Clearance Lamp LED 12-36V, RED with reflector, flat mounting and angle bracket, a loom lenght 0,5m.
FT-078 C LED QS075	Clearance Lamp LED 12-36V, RED with reflector, flat mounting and angle bracket, a loom lenght 0,5m and connector QS075.
FT-078 C LED QS150	Clearance Lamp LED 12-36V, RED with reflector, flat mounting and angle bracket a loom lenght 0,5m and connector QS150.
FT-078 Z LED	Clearance Lamp LED 12-36V, YELLOW with reflector, flat mounting and angle bracket, a loom lenght 0,5m.
FT-078 Z LED QS075	Clearance Lamp LED 12-36V, YELLOW with reflector, flat mounting and angle bracket, a loom lenght 0,5m and connector QS075.
FT-078 Z LED QS150	Clearance Lamp LED 12-36V, YELLOW with reflector, flat mounting and angle bracket, a loom lenght 0,5m and connector QS150.